



Pro 16h+

Wide Format Hybrid Inkjet Printer

The **ultimate** wide-format  
business tool



# Boost your production + image quality

The EFI™ Pro 16h+ production-level, hybrid flatbed/roll-fed LED inkjet printer is the ultimate business tool if you want to expand into higher-margin wide-format graphics or upgrade your current capabilities. The Pro 16h+ printer delivers outstanding image quality at production speeds up to 50% faster than the original model, white ink, and up to five-layer printing in any colour in a single pass. Plus, new high-performance EFI ProGraphics™+ Series LED Inks print on a wide range of substrates for nearly limitless applications – all while keeping the total cost of ownership low.



# + business growth

## Ultimate hybrid production-level printing for faster job turns

- Versatile 165 cm wide hybrid flatbed/roll-fed printer
- Rigid and flexible media support up to 5.08 cm thick with quick and easy changeover
- Production quality printing at 29 m<sup>2</sup>/hr
- Front and back media pressure rollers for handling a wider range of media
- Semi-continuous board feeding with print job start from the front or back of the printer for easy operation
- Advanced, four-chamber media-platen vacuum system with independent power controls ensures efficient hold down, no media movement, and easy transition between jobs
- Dual movable foot pedal to start the vacuum from any side of the printer
- Quick printer recovery if carriage crashes with media
- Embedded Fiery® proServer Core digital front end (DFE) with FAST RIP acceleration technology that eliminates idle print downtime, and RIP and print-on-demand functionality or the ability to print pre-ripped files

## Ultimate image quality for increased customer satisfaction

- Four colours plus two white channels come standard
- Resolution up to 1200 x 1200 dpi
- True variable drop greyscale printing with 5pL drop sizes for saturated colours, smooth gradients, and fine text
- Magnetic linear drive control and high-volume ink jetting at an accurate level ensure precise dot placement for sharper lines and text and less overspray

## Ultimate capabilities for more applications and higher profits

- CMYK plus EFI best-in-class white ink in opacity and colour gradient
- Multilayer printing in any colour up to five layers in a single pass for more high-value applications
- EFI LED technology for more profit opportunities with the ability to print more premium-margin jobs while lowering your operating costs and environmental footprint:
  - Extends your range of supported substrates to include thinner/lower cost and heat-sensitive speciality media
  - Increases uptime and productivity with instant on/off lamps and less maintenance
  - Drives down operating costs with less energy consumption and fewer consumables
  - Reduces media and ink waste with consistent colour and simple operation
  - Offers a greener print solution with low VOC inks, lower power consumption, less waste, and fewer consumables

## Ultimate performance with EFI ProGraphics+ Series LED Inks

- Remarkable open time - eliminating the need to purge or wipe printheads between jobs
- Improved jetting performance increases uptime and reliability
- Improved adhesion, elongation, and water resistance, while retaining the same surface cure as the ProGraphics POP UV inks
- Environmentally friendly: Do not contain heavy metals, virtually no VOC emissions, TPO and THFA free, and formulated to meet EU regulations

## TECHNICAL SPECIFICATIONS

Media handling		Productivity			
Maximum printing width	165 cm	Express - 1 pass	129 m <sup>2</sup> /hr		
Maximum image width	162.6 cm full-bleed printing	Distant - 2 pass	80 m <sup>2</sup> /hr		
Maximum media thickness	5.08 cm	Outdoor - 4 pass	42 m <sup>2</sup> /hr		
Four-zone, user-selectable vacuum system		Production - 6 pass	29 m <sup>2</sup> /hr		
Maximum rigid and roll media weight:	45.4 kg	POP - 8 pass	22 m <sup>2</sup> /hr		
Maximum roll diameter:	22.9 cm	High Quality - 12 pass	15 m <sup>2</sup> /hr		
Modular table design for scalable rigid printing depth		Ultra Quality - 16 pass	11 m <sup>2</sup> /hr		
Environmental conditions					
Compressed air:	Not required				
Operating temperature:	18 °C to 27 °C				
Humidity:	40% to 80% (non-condensing)				
Dimensions (H x W x L) with one set of tables:	348 cm x 241 cm x 163 cm				
Weight:	1,235 kg, including tables and rollers 891 kg without peripherals				
Electrical:	208-240 VAC, single phase, 50/60 Hz, 30 Amps				
Fiery digital front end					
Ships with an embedded Fiery® proServer Core					
Formats					
All popular desktop files formats, including PostScript® 3 <sup>TM</sup> , EPS, TIFF, PDF, and RGB/CMYK					

## Let's be brilliant. Together.

We understand you want breakthrough technologies to lead you through your digital journey. That's why we're passionate about driving your business growth with a scalable portfolio of products, solutions, services, support, and world-class partnerships for the manufacturing of signage, packaging, textiles, ceramic tiles, and building materials with a wide range of printers and inks. Our unwavering commitment is to increase your profits, cut costs, improve productivity, and optimise efficiency — job after job, year after year. We're obsessed with your success. And we definitely believe we have the right people, technology and experience to help your business achieve its goals. Visit [www.efi.com](http://www.efi.com) or send an email to [info@efi.com](mailto:info@efi.com) for more information.



Nothing herein should be construed as a warranty in addition to the express warranty statement provided with EFI products and services.

BDR, Cretachrom, Cretaprint, the Cretaprint logo, Cretaprinter, Cretaroller, Divisional Graphics, Distancing Graphics, EFI, the EFI logo, Electronics For Imaging, FabriVU, Fast-4, Inèdit, Inktensity, Inkware, neoCatalog, neoStampa, neoTextil, PressVu, ProGraphics, Rialco, Riaplas, SDC, SafeGuard Graphics, UltraDrop, UltraPress, UltraTex, UltraVu, UV Series 50, VUTEk, and the VUTEk logo are trademarks or registered trademarks of Electronics For Imaging, Inc. and/or its wholly owned subsidiaries in the U.S. and/or certain other countries.

All other terms and product names may be trademarks or registered trademarks of their respective owners and are hereby acknowledged.